

## 301IRFS SPECIFICATIONS

### Infrared Refrigerant Gas Detector



General Specification		
<b>Use</b>	Infrared refrigerant sensor to be used with the 301EM-20	
<b>Gases Detected</b>	R11, R22, R123, R125, R134A, R404A, R407C, R410A, R507A, 514A, 1233ZD, 1234ZE	
<b>Sensing Technology</b>	Infrared sensor	
<b>Measurement Range</b>	0-1,000 ppm	
<b>Resolution</b>	1 ppm	
<b>Deadband</b>	20 ppm	
<b>Accuracy</b>	± 40 ppm @ 500 ppm	
<b>Response Time (T90)</b>	60 seconds	
<b>Warmup time</b>	15 minutes	
<b>Operating Environment</b>	Indoor Use	
<b>Operating Temperature Range:</b>	32° to 100°F (0° to 40°C)	
<b>Operating Humidity Range:</b>	0 to 95% RH (non-condensing)	
<b>Enclosure</b>	ABS – Polycarbonate	
<b>Size</b>	4 (H) x 11 (W) x 2.5 (D) in. (10.2 x 28 x 6.3 cm)	
<b>Weight</b>	2.33 lbs. (0.603 kg)	
<b>Visual Indicators</b>	Normal Operation	LED blinks according to the sensor addresses on the 301EM-20
	Failure Indication	LED will remain on

#### Find out more

[www.honeywellanalytics.com](http://www.honeywellanalytics.com)

Toll free: 800 538 0363

#### Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.