

# UNI-T®

## UT230B SERIES Power Socket

UT230B-EU / UT230B-US



EN 61010-1  
UL 61010-1  
EN 61326-1

Intertek



■ UT230B-EU



■ UT230B-US

### SPECIFICATIONS

Specifications	Range	UT230B-EU	UT230B-US
Model		UT230B-EU	UT230B-US
Voltage	100.0V~260.0V	±1%	±1%
Current	0A~16.00A	±1%	
	0A~15.00A		±1%
Operating Frequency	45Hz	±1%	±1%
Power	0~3680W	±1%	±1%
Power Factor	0~1.00	±2%	±2%
Energy consumption	0~9999KWh	±1%	±1%
<b>Feature</b>			
Unit Price of Electricity	0.00~99.99 (\$/kWh)	✓	✓
Acumulative Time	0 minute~9999Days	✓	✓
Acumulative Charge	0~9999\$	✓	✓
CO2 Display	0~9999kg	✓	✓
Power Consumption	<0.4W	✓	✓
Overload indication	>16A	✓	
	>15A		✓

### GENERAL CHARACTERISTICS

Power	3.0 V Button Battery
Product Color	White
Product Net Weight	140g
Product Size	130mm × 65mm × 59 mm
Standard Accessories	Batteries
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	48PCs
Standard Carton Measurement	445mm × 405mm × 395mm (0.071 CBM Per Standard Carton)
Standard Carton Gross Weight	11.7 kg

# UNI-T®

## UT230B SERIES Power Socket

UT230B-AU / UT230B-UK



Intertek



■ UT230B-AU



■ UT230B-UK

### SPECIFICATIONS

Specifications	Range	UT230B-AU	UT230B-UK
Model		UT230B-AU	UT230B-UK
Voltage	100.0V~260.0V	±1%	±1%
Current	0A~15.00A 0A~13.00A	±1%	±1%
Operating Frequency	45Hz	±1%	±1%
Power	0~3680W	±1%	±1%
Power Factor	0~1.00	±2%	±2%
Energy consumption	0~9999KWh	±1%	±1%
Feature			
Unit Price of Electricity	0.00~99.99 (\$/kWh)	✓	✓
Acumulative Time	0 minute~9999Days	✓	✓
Acumulative Charge	0~9999\$	✓	✓
CO2 Display	0~9999kg	✓	✓
Power Consumption	<0.4W	✓	✓
Overload indication	>15A	✓	
	>13A		✓

### GENERAL CHARACTERISTICS

Power	3.0V Button Battery
Product Color	White
Product Net Weight	140g
Product Size	130mm × 65mm × 59mm
Standard Accessories	Batteries
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	48PCs
Standard Carton Measurement	445mm × 405mm × 395mm (0.071 CBM Per Standard Carton)
Standard Carton Gross Weight	11.7 kg

# NEW



■ UT230B-IND

### SPECIFICATIONS

Specifications	Range	Best Accuracy
Model		UT230B-IND
Voltage	100.0V~260.0V	±1%
Current	0A~6.00A	±1%
Operating Frequency	50Hz	±1%
Power	0~1380W	±1%
Power factor	0~1.00	±2%
Energy consumption	0~9999KWh	±1%
Feature		
Unit Price of Electricity	0.00~99.99 (\$/kWh)	✓
Cumulative Time	0 minute~9999Days	✓
Cumulative Charge	0~9999\$	✓
CO2 Display	0~9999kg	✓
Product Power Consumption	<0.4W	✓
Overload indication	>6A	✓

### GENERAL CHARACTERISTICS

Power	3.0 V Button Battery
Product Color	White
Product Net Weight	140g
Product Size	130mm × 65mm × 59mm
Standard Accessories	Batteries
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	48PCs
Standard Carton Measurement	445mm × 405mm × 395mm (0.071 CBM Per Standard Carton)
Standard Carton Gross Weight	11.7kg