

DIGITAL MULTIMETER

MY60/MY61/MY62

MY60

VOLTAGE AC 750V
DC 1000V

CURRENT AC 10A
DC 10A



hFE

Apo



MY61

VOLTAGE AC 750V
DC 1000V

CURRENT AC 10A
DC 10A



hFE

Apo



MY62

VOLTAGE AC 750V
DC 1000V

CURRENT AC 10A
DC 10A



hFE

Apo



Features:

- ▶ Rugged Shell Design
- ▶ Large Digital LCD Display
- ▶ Tests AC/DC Voltage and Current, Resistance, Capacitance and Frequency
- ▶ Transistor Check, Diode and Continuity Test
- ▶ Type-K thermocouple contact temperature measurement (MY62)
- ▶ Data Hold and Auto Power Off

EMC
LVD



Specifications

		MY60	MY61	MY62
Specifications	Range	Accuracy		
DC Voltage	200mV/2V/20V/200V	±(0.5%+3)	±(0.5%+3)	±(0.5%+3)
	1000V	±(0.8%+3)	±(0.8%+3)	±(0.8%+3)
AC Voltage	200mV	±(1.2%+3)	±(0.8%+3)	±(0.8%+3)
	2V/20V/200V	±(0.8%+3)	±(0.8%+3)	±(0.8%+3)
	750V	±(1.2%+3)	±(1.2%+3)	±(1.2%+3)
DC Current	20µA	±(2.0%+5)		
	200µA	±(0.8%+3)		
	2mA/20mA/200mA	±(1.5%+1)	±(1.5%+1)	±(1.5%+1)
AC Current	10A	±(2.0%+5)	±(2.0%+5)	±(2.0%+5)
	20µA/200µA	±(1.8%+5)		
	2mA/20mA/200mA	±(1.8%+5)	±(1.8%+5)	±(1.8%+5)
Resistance	10A	±(3.0%+5)	±(3.0%+5)	±(3.0%+5)
	200Ω/2KΩ/20KΩ/200KΩ/2MΩ	±(0.8%+3)	±(0.8%+3)	±(0.8%+3)
	20MΩ	±(1.0%+5)	±(1.0%+5)	±(1.0%+5)
Capacitance	200 MΩ	±(6.0%+10)	±(6.0%+10)	±(6.0%+10)
	2nF/20nF/200nF/2µF		±(4.0%+3)	±(4.0%+3)
Temperature(°C)	100µF		±(6.0%+10)	±(6.0%+10)
	-20°C~1000°C			±(2%+2)
Features				
Display	counts	2000	2000	2000
Transistor hFE	0~1000	●	●	●
Diode	2.7V	●	●	●
Continuity Buzzer	<50Ω	●	●	●
Data Hold		●	●	●
Apo	Auto Power Off	●	●	●
LBD	Low Battery Display	●	●	●
General				
Power Supply	1×9V 6F22 Battery			
Product Size	195mm×95mm×55mm/7.67"×3.74"×2.16"			
Product Weight	366g/0.8lb			
Safety Rating	CE ETL CAT.II 1000V CAT.III 600V RoHS			