

TES-1339**Light Meter Pro.**

Display	Dual display 4 digit LCD read out.
Measuring Range	99.99, 999.9, 9999, 99990, 999900 Lux 9.999, 99.99, 999.9, 9999, 99990 fc Auto rangeing (5 step) (1 fc = 10.76 Lux)
Overrange Display	OL is displayed
Resolution	0.01 Lux, 0.001 fc
Accuracy	± 3% rdg ± 5dgt (Calibrated to standard incandescent lamp, 2856° K)
CIE photopic f ' 1	≤ 6 %
Temperature Characteristics	± 0.1%/ °C
Measuring Rate	Approximately 5 time/sec
Photosensor	Silicon photodiodes
Data Memory Capacity	50 sets. (Direct reading from LCD display)
Operating / Storage Conditions	0 °C ~ 50 °C <80% RH -10 °C ~ 60 °C <70%RH
Power Source	6 pcs AAA size Battery
Battery Life (typical)	100 hours
Photosensor Lead Length	150 cm (approx.)
Photosensor Dimensions	100(L) × 60(W) × 27(H)mm
Dimension	150(L) × 72(W) × 33(H)mm
Weight	250g
Accessories	Carrying case, Instruction manual, Battery

TES-1339R**Data Logger Light Meter Pro.**

Display	Dual display 4 digit LCD read out.
Measuring Range	99.99, 999.9, 9999, 99990, 999900 Lux 9.292, 92.92, 929.2, 9292, 92927 fc Auto rangeing (5 step) (1 fc = 10.76 Lux)
Overrange Display	OL is displayed
Resolution	0.01 Lux, 0.001 fc
Accuracy	± 3% rdg ± 5dgt (Calibrated to standard incandescent lamp, 2856° K)
CIE photopic f ' 1	≤ 6 %
Temperature Characteristics	± 0.1%/ °C
Measuring Rate	Approximately 5 time/sec
Photosensor	Silicon photodiodes
Data Memory Capacity	99 sets. (Direct reading from LCD display)
Data Logger Capacity	40000 sets.
Operating / Storage Conditions	0 °C ~ 50 °C <80% RH -10 °C ~ 60 °C <70%RH
Power Source	6 pcs AAA size Battery
Battery Life (typical)	100 hours
Photosensor Lead Length	150 cm (approx.)
Photosensor Dimensions	92(L) × 60(W) × 29(H)mm
Dimension	150(L) × 72(W) × 35(H)mm
Weight	320g
Accessories	Carrying case, Instruction manual, Battery, CD software, RS232 Cable.