

UT201/UT202/UT202A SERIES CLAMP METER

UT201

Features:

- LCD display, 1999 counts
- Auto ranging
- Diode check
- Continuity check with buzzer
- Max hold
- Data hold
- Low battery indication
- Auto power off

Standard accessories

- 1) Test leads
- 2) Batteries
- 3) Thermocouple (UT202 only)
- 4) Carrying bag
- 5) Operation manual

Specifications

FUNCTION	MEASUREMENT RANGE	BEST ACCURACY
DC Voltage	200m/2/20/200/600V	+/-0.8%+1digit
AC Voltage	2/20/200/600V	+/-1.2%+5digit
AC Current	2/20/200/400A	+/-1.5%+5digit
Resistance	200/2k/20k/200k/2M/200MOhm	+/-1%+2digit
Diode Check		
Continuity Check		
Max Jaw Diameter	Ø28mm	
Size/Weight	210x75.6x30mm/220g	
Power Source	1.5V AAA x 2	

UT202

Features:

- LCD display, 1999 counts
- Auto ranging
- Diode check
- Continuity check with buzzer
- Temperature test
- Max hold
- Data hold
- Low battery indication
- Auto power off

Specifications

FUNCTION	MEASUREMENT RANGE	BEST ACCURACY
DC Voltage	200m/2/20/200/600V	+/-0.8%+1digit
AC Voltage	2/20/200/600V	+/-1.2%+5digit
AC Current	2/20/200/400A	+/-1.5%+5digit
Resistance	200/2k/20k/200k/2M/20MOhm	+/-1%+2digit
Temperature	-40°C ~ 1000°C -40°F ~ 1832°F	+/-1%+3digit +/-1%+6digit
Diode Check		
Continuity Check		
Max Jaw Diameter	Ø28mm	
Size/Weight	210x75.6x30mm/220g	
Power Source	1.5V AAA x 2	



UT201

UT202A

Features:

- LCD display, 1999 counts
- Manual/auto ranging
- Diode check
- Continuity check with buzzer
- Max hold
- Data hold
- Low battery indication

Specifications

FUNCTION	MEASUREMENT RANGE	BEST ACCURACY
DC Voltage	200m/2/20/200/600V	+/-0.8%+1digit
AC Voltage	2/20/200/600V	+/-1.2%+5digit
AC Current	20/200/600A	+/-1.5%+5digit
Resistance	200/2k/20k/200k/2M/20MOhm	+/-1%+2digit
Diode Check		
Continuity Check		
Max Jaw Diameter	Ø28mm	
Size/Weight	210x75.6x30mm/200g	
Power Source	9V 6F22 x 1	

