



UT07A-AU
UT07B-AU

EN 61010-1
EN 61326-1



■ UT07A-UK



■ UT07A-AU



■ UT07B-AU

SPECIFICATIONS

Specifications	Range	Best Accuracy		
		UT07A-UK	UT07A-AU	UT07B-AU
Model		UT07A-UK	UT07A-AU	UT07B-AU
Operating Voltage	230VAC	✓	✓	✓
Operating Power	0.7W	✓	✓	✓
Working Frequency	50~60Hz	✓	✓	✓
RCD	About 30mA			✓
Indications	Correct	✓	✓	✓
	Open Ground	✓	✓	✓
	Hot/GND Reverse	✓	✓	✓
	Hot/NEU Reverse	✓	✓	✓
	Open Neutral	✓	✓	✓
Features				
LED Indications		✓	✓	✓
RCD Test				✓

GENERAL CHARACTERISTICS

Power	230VAC
Product Color	Red and Grey
Product Net Weight	UT07A-UK- 64g, UT07A-AU, UT07B-AU- 58g
Product Size	65mm × 65mm × 40mm
Standard Accessories	NO
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	96 PCs
Standard Carton Measurement	525mm x 285mm x 350mm(0.052CBM Per Standard Carton)
Standard Carton Gross Weight	UT07A-UK-10.3 kg, UT07A-AU, UT07B-AU- 9.7 kg

NEW



EN 61010-1
EN 61326-1



■ UT07A-EU



■ UT07B-EU

SPECIFICATIONS

Specifications	Best Accuracy	
Model	UT07A-EU	UT07B-EU
Rated Current	10A	10A
Rated Voltage	230V AC	230V AC
Operating Current	<18mA	<18mA
RCD		300mA
Description		
OK, leakage test passed	✓	✓
OK	✓	✓
Ground missing	✓	✓
Live missing	✓	✓
Neutral missing	✓	✓
Live/Ground inverted	✓	✓
Live/Ground inverted and Ground missing	✓	✓

GENERAL CHARACTERISTICS

Power	230VAC
Product Color	Red and Grey
Product Net Weight	UT07A-EU- 79g, UT07B-EU- 80.5g
Product Size (LxWxH)	65mm×65mm×61mm
Standard Accessories	NO
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	96 PCs
Standard Carton Measurement	525mm x 285mm x 350mm(0.052CBM Per Standard Carton)
Standard Carton Gross Weight	UT07A-EU- 11.6 kg, UT07B-EU- 11.8 kg

NEW



■ UT07A-IND



■ UT07B-IND



■ UT07D-IND

SPECIFICATIONS

Specifications	Best Accuracy		
	UT07A-IND	UT07B-IND	UT07D-IND
Model	UT07A-IND	UT07B-IND	UT07D-IND
Socket Current	6A	6A	16A
Socket Voltage	250V AC	250V AC	250V AC
Operating Voltage	220V/50Hz	220V/50Hz	220V/50Hz
Operating Current	<18mA	<18mA	<18mA
RCD		30mA	
Description			
Correct	✓	✓	✓
Ground missing	✓	✓	✓
Live/Ground inverted	✓	✓	✓
Live/Neutral inverted	✓	✓	✓
Neutral missing	✓	✓	✓

GENERAL CHARACTERISTICS

Power	230VAC
Product Color	Red and Grey
Product Net Weight	UT07A-IND- 64g, UT07B-IND- 65.5g, UT07D-IND- 72g
Product Size (LxWxH)	65mm×65mm×61mm
Standard Accessories	NO
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	96 PCs
Standard Carton Measurement	525mm x 285mm x 350mm(0.052CBM Per Standard Carton)
Standard Carton Gross Weight	UT07A-IND-10.2 kg, UT07B-IND- 10.4 kg, UT07D-IND- 11 kg



UL61010-1
EN61326-1
EN61010-1



■ UT08A

SPECIFICATIONS

Specifications	Range	UT08A	UT08B
Model		UT08A	UT08B
Operating Voltage	110~125VAC	✓	✓
Operating Power	0.3W	✓	✓
Working Frequency	50~60Hz	✓	✓
GFCI	6~9mA		✓
Indications	Open Ground	✓	✓
	Open Neutral	✓	✓
	Open Hot	✓	✓
	Hot/GND Reverse	✓	✓
	Hot/NEU Reverse	✓	✓
	Correct	✓	✓
Features			
LED Indications		✓	✓
GFCI			✓



■ UT08B

GENERAL CHARACTERISTICS

Power	110~125VAC
Product Color	Red and Grey
Product Net Weight	About 36g
Product Size	55mm × 44mm × 27mm
Standard Accessories	NO
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	80 PCs
Standard Carton Measurement	480mm × 385mm × 240mm (0.048 CBM Per Standard Carton)
Standard Carton Gross Weight	5 kg