

DIGITAL TACHOMETER

MODEL RM-1500/RM-1501

- 5 Digits LCD Display
- Range 10.0~99,999RPM
- Measuring Distance
50~300mm
- Combination type for
non-contact and contact
measurements
- Counter (0~99999)
- RS-232 (RM-1501)



RM-1500/RM-1501

Specifications for RM-1500/RM-1501 (23°C±5°C)

RPM (non-contact measuring , Autorange):

Range	Resolution	Accuracy
10.0~6,000.0rpm	0.1rpm	+/-0.01%±1digit
6,000.0~9,999.9rpm	0.1rpm	+/-0.02%±1digit
1,000~12,000rpm	1rpm	+/-0.02%±1digit
12,000~30,000rpm	1rpm	+/-0.05%±1digit
Over 30,000rpm	1rpm	+/-0.1%±1digit

RPM (contact measuring , Autorange):

Range	Resolution	Accuracy
10.0~6,000.0rpm	0.1rpm	+/-0.01%±1digit
6,000.0~9,999.9rpm	0.1rpm	+/-0.02%±1digit
1,000~12,000rpm	1rpm	+/-0.02%±1digit
12,000~30,000rpm	1rpm	+/-0.05%±1digit
Over 30,000rpm	1rpm	+/-0.1%±1digit

General Specification:

Battery:	Four 1.5V battery (AA, UM3)
Time Base:	4.000MHz Quartz Crystal
Operating Temperature:	0°C ~ 50°C (32°F ~ 122°F)
Reflective light:	Red LED
Size:	6.8"(L) x 2.5"(W) x 1.4"(H) 175mm(L) x 65mm(W) x 36mm(H)
Weight:	250g (including battery)

Option:

Instruction Manual x 1 Contact Adaptor

TES Electrical Electronic Corp.
7F, No. 31, Lane 513, Rui Guang Road,
Neihu Dist. Taipei, Taiwan, R.O.C.
TEL : 886-2-2799-3660
FAX : 886-2-2799-5099
E-mail : tes@ms9.hinet.net

[\[PREVIOUS MODEL\]](#) [\[PRODUCT LIST\]](#) [\[HOME\]](#)