

TES-1319 Thermometer



FEATURES

- Type "K" Thermocouple Input.
- Switchable Resolution 0.1° / 1° .
- With °C & °F switching.
- Max / MIN Function.
- Data Hold Function.
- Flip-up stand.




SPECIFICATION

Measuring Rang	- 50 °C ~ 1350°C , -58 °F ~ 1999 °F
Sensor	K Type Thermocouple
Input	Single Channe
Resolution	- 50 °C ~ 199.9 °C.....0.1 °C , - 50 °F ~ 199.9 °F.....0.1 °F (Others 1 °C/1 °F)
Accuracy	- 50 °C ~ 199.9 °C... +/- (0.3%rdg + 1 °C) - 50 °F ~ 199.9 °F... +/- (0.3%rdg + 2 °F) - 50 °C ~ 1000 °C... +/- (0.5%rdg + 1 °C) - 50 °F ~ 1999 °F... +/- (0.5%rdg + 2 °F) 1001 °C ~ 1300 °C... +/- (0.75%rdg + 1 °C)
Temperature Coefficient	Less that 0.1 times the applicable accuracy specification per °C (°F)
Input Protection	60V DC or 24 Vrms AC maximum input voltage on any Combination of input Connector
Sampling Rate	2.5 times / sec
Operating / Storage Conditions	0 °C ~ 40 °C <80%RH , - 10 °C ~ 60 °C < 70%RH
Power Source	6 pcs AAA size Battery

Size	135mm(L) x 72mm(W) x 31mm(H)
Weight	235g
Accessories	Battery, Instruction, Manual

Close Window

 TES Electrical Electronic Corp.

Office:7F, NO.31, Lane 513,Rui Guang Road, Neihu Dist., Taipei,
Taiwan, R.O.C.
TEL:886-2-2799-3660 FAX:886-2-2799-5099 E-Mail:tes@ms9.hinet.net